

MULTI-PORT PLASTIC BALL VALVES (3 / 4 Way) PVC - ABS - PP				
Designed for diverting liquid flows along alternative routes/ports Chemicals and water applications are typical uses subject to material of valve etc. Compatibility. All valves are the Ball Plug Type and have PTFE seats & EP seals WNS				
Type (1) = PVC True Union valves with bottom entry 'L' Port socket end. Lockable standard.				
Type (2) = PVC True Union valves with horizontal entry 'T' Port socket end. Lockable. configuration.				
Type (3) = PP 2 part union valves with bottom entry 'L' Port connection standard. (Any End).				
Type (4) = PP Single Union valves with bottom entry 'L' Port OEM economy type. (BSP Female)				
Type (1) PVC		Type (2) PVC		Type (3) PP
SOCKET ENDS		FUSION / BSP ENDS		BSP ENDS
<a href="#">3/8" - 2" Data Sheet</a>		<a href="#">3" - 4" Data Sheet</a>		<a href="#">1/4" - 2" Data Sheet</a>
Ports	'L Port'	'T Port' (HORI)	'L Port'	'L Port' (ECONOMY)
Pressure	10 BAR	10 BAR	10 BAR	8 BAR
Size	Ref : 10P60A	Ref : 10P65A	Ref : 10P20	Ref : 10P21
1/4"	-	-	-	£22.50
3/8"	£95.55	£95.55	-	-
1/2"	£95.55	£95.55	£81.32	£17.00
3/4"	£96.60	£96.60	£94.16	£18.00
1"	£96.60	£96.60	£99.51	£21.00
1.1/4"	£148.05	£148.05	£116.63	£35.00
1.1/2"	£149.10	£149.10	£155.15	£47.00
2"	£183.75	£183.75	£178.69	£68.00
2.1/2"	-	-	-	£ 192.00 SANDWICH TYPE *
3"	£871.50	£871.50	-	£ 202.00 SANDWICH TYPE *
4"	£1,580.25	£1,580.25	-	<a href="#">3" - 4" * Data Sheet</a>
<a href="#">Electric Op-&gt; Page 38</a>			On Application 2" 'T' Port GFPP 3 way valve= Ref 10P2220T.	£383.90
<a href="#">Pneumatic Op-&gt;Page 38</a>			On Application 2" 'L' Port GFPP 4 way valve= Ref 10P2221L.	£462.00
1/4" = NPT Threaded (Special Compact Style Valve).				
Electric & Pneumatic available above --> plus modulating 0 to 10 volt control if required per special requirement.				

PVC BUTTERFLY VALVE TO 250mm (PP to 24")													
This light valve give efficient operation combined with economic cost & corrosion resistance. A slim disc gives good flow qualities +													
the valve can also be fitted with sockets for ease of cementing straight into pipe with minimum fuss. EPDM seals are standard													
(FPM is extra). Spring acting lever has limit travel positioning notches. Gearboxes for all sizes possible. Do not over torque/tighten bolts when mounting. Options for Electric/Pneumatic Actuation also) PVC Spindle and metal insert.													
Size	Material	Dimension (SEE BELOW FOR REFERENCE)										Ref:10P163	Ref:10P163M
		A	B	C	E	F	H	L	Nm	Bar	Kg>	Wafer	Mounted
2"	50mm PVC	193	165	110	28	18*4	48	197	25	10	2	£144.10	£180.40
2.5"	65mm PVC	193	165	110	28	Wafer	48	197	25	10	2	£144.10	£184.80
3"	80mm PVC	227	130	126	30		53	260	55	10	3	£168.30	£244.20
4"	100mm PVC	271	150	157	30		60	260	100	6	4	£188.10	£279.40
5"	125mm PVC	297	250	172	30		66	260	120	6	4	£218.90	£335.50
6"	150mm PVC	327	285	185	30		72	260	140	4	6	£268.40	£473.00
8"	200mm PVC	400	340	230	30		73	390	340	4	9	£398.20	£697.40
10"	250mm PVC	450	320	250	35		106	GBx	450	3	16	£792.00	TBA
12"	300mm PP	522	367	270	60		20*16	126	GBx	800	3	33	£1,633.91
14"	350mm PP	560	420	300	60	20*16	126	GBx	800	3	38	£3,630.00	-
16"	400mm PP	665	604	363	60	20*20	169	GBx	1600	3	69	£5,643.00	-
18"	450mm PP	675	634	365	70	20*20	181	GBx	1600	2	90	TBA	-
20"	500mm PP	769	728	405	70	20*20	191	GBx	2000	2	90	TBA	-
24"	600mm PP	875	850	450	70	20*20	209	GBx	2400	1		TBA	-
Can be supplied complete with Stub Flanges Backing Rings & Bolts assembled (i.e. mounted)													
All dimensions are in mm. Valve is based on NP10 flanges but has elongated holes for BS or ANSI types.													
* = PP types. G = Gear Boxed. PP types is changed construction.													
Above are full bodied wafer types and can offer cheaper basic wafer types to 8" on call.													

